

**CARATTERISTICHE TECNICHE POMPE SERIE S  
TECHNICAL CHARACTERISTICS PUMPS RANGE S**

Tipo Type	Capacità Capacity (L/H)	Conessioni* Connections*	R.P.M.	kW Assorbiti kW Absorbed			Peso Weight bare shaft (kg)
				5 bar	10 bar	15 bar	
S 05	300	¾" BSP*	1.450	0.07	0.14	0.21	3,5
S 10	600	¾" BSP*	1.450	0.14	0.28	0.43	4
S 15	900	¾" BSP*	1.450	0.21	0.43	0.64	5
S 25	1500	¾" BSP*	1.450	0.36	0.71	1.07	8
S 50	3000	1" BSP*	1.450	0.71	1.42	2.13	13
S 70	4200	1" BSP*	1.450	1.00	2.00	2.99	19
S 100	6000	2" BSP*	1.450	1.42	2.85	4.27	27
S 150	9000	2" BSP*	1.450	2.13	4.27	6.40	30
S 200	12000	2" BSP*	1.450	2.85	5.69	8.54	35
S 300	18000	2" BSP*	1.450	4.27	8.10	-	39
S 320	19200	2 ½" SAE	1.450	4.55	9.11	13.66	43
S 400	24000	2 ½" SAE	1.450	5.69	11.39	17.08	48
S 500	30000	2 ½" SAE	1.450	7.12	14.23	21.35	55
S 600	36000	3" SAE	1.450	8.54	17.08	25.62	60
S 800	48000	3" SAE	1.450	11.39	22.77	-	75
S M00	60000	3" SAE	1.450	14.23	28.47	-	80

\*On request SAE flanges WELD ON/ Su richiesta flange SAE WELD ON