

**CARATTERISTICHE TECNICHE POMPE SERIE SK
TECHNICAL CHARACTERISTICS PUMPS RANGE SK**

| Tipo Type | Capacità Capacity (L/H) | Conessioni* Connections* | R.P.M. | kW Assorbiti kW Absorbed | | | Peso Weight bare shaft (kg) |
|--------------|----------------------------|-----------------------------|--------|-----------------------------|--------|--------|-----------------------------------|
| | | | | 5 bar | 10 bar | 15 bar | |
| SK 05 | 300 | ¾" BSP* | 1.450 | 0.07 | 0.14 | 0.21 | 3,5 |
| SK 10 | 600 | ¾" BSP* | 1.450 | 0.14 | 0.28 | 0.43 | 4 |
| SK 15 | 900 | ¾" BSP* | 1.450 | 0.21 | 0.43 | 0.64 | 5 |
| SK 25 | 1500 | ¾" BSP* | 1.450 | 0.36 | 0.71 | 1.07 | 8 |
| SK 50 | 3000 | 1" BSP* | 1.450 | 0.71 | 1.42 | 2.13 | 13 |
| SK 70 | 4200 | 1" BSP* | 1.450 | 1.00 | 2.00 | 2.99 | 19 |
| SK 100 | 6000 | 2" BSP* | 1.450 | 1.42 | 2.85 | 4.27 | 27 |
| SK 150 | 9000 | 2" BSP* | 1.450 | 2.13 | 4.27 | 6.40 | 30 |
| SK 200 | 12000 | 2" BSP* | 1.450 | 2.85 | 5.69 | 8.54 | 35 |
| SK 320 | 19200 | 2 ½" SAE | 1.450 | 4.55 | 9.11 | 13.66 | 43 |
| SK 400 | 24000 | 2 ½" SAE | 1.450 | 5.69 | 11.39 | 17.08 | 48 |
| SK 600 | 36000 | 3" SAE | 1.450 | 8.54 | 17.08 | 25.62 | 60 |
| SK 800 | 48000 | 3" SAE | 1.450 | 11.39 | 22.77 | - | 75 |

*On request SAE flanges WELD ON/ Su richiesta flange SAE WELD ON